



BURNDY Catalog Number
UPC Number

YSD25R25R
 7818100139222
 1/0 TO 1/0 AL/CU/ACSR SE,6-1
 STR
 Active

Description
Status

Web Use
 BURNDY Product Line

General

Product Description

Aluminum compression sleeve with solid center barrier, Designed for commercial and heavy residential services, Die index:249,K-840
 Y

Prefilled (Oxide Inhibitor)

Conductor(s)

- ACSR Size (Side A) - Range 1/0 (6/1) Raven AWG
- ACSR Size (Side B) - Range 1/0 (6/1) Raven AWG
- Copper Str Size(Side B) - Range 1/0 -2/0 AWG
- ACCC 6201 Size (Side B) - Range 123.3 (7) kcmil
- Aluminum Size (Side A) - Range 1/0 AWG-2/0 AWG
- ACCC 5005 Size (Side B) - Range 123.3 (7) kcmil
- ACCC 6201 Size (Side A) - Range 123.3 (7) kcmil
- ACCC 5005 Size (Side A) - Range 123.3 (7) kcmil
- Copper Str Size (Side A) - Range 1/0 -2/0 AWG
- Aluminum Size (Side B) - Range 1/0 AWG-2/0 AWG


Approvals / Certifications

- UL Listed N
- CSA Certified N
- ROHS Compatible Compliant
- UL Recognized N
- CULUS N

Physical

- Color Code (Side A) Yellow
- Type of Plating Unplated
- Color Code (Side B) Yellow
- Plated (Yes or No) N
- Index Number 249,K-840
- Product Material Aluminum
- Insulated (Yes or No) N

Documentation



For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
 Monday - Friday
 Phone: 800-346-4175