

YCS25

by Burndy
Catalog ID: YCS25



CU loop splice connector designed to withstand jumper loop tensile and vibration stresses up to 60 percentage RBS, -3/8 IN L.

Features: Loop HYSPLICE Connector Designed To Withstand Jumper Loop Tensile And Vibration Stresses, Made Of Pure Copper Tubing, Installed With Standard HYSPLICE Tools And Dies, Die Index: 165 Element A, Tools, Die Set Catalog Number, And (number Of Crimps): MD6, MD7 Tool, W165 Die, (3), Y750, Y35 Tool, U165 Die, (3), Y45 Tool, U165 Die With PT-6515 Adapter, (3), Y46 Tool, U165 Die With PUADP-1 Adapter, (3), Conductor Type: Copper

Product Details

General

Application	For Copper Conductors
Connector Type	Splice
Construction Material - Main	Copper
Die Index	165
Material	Copper
Plated	N
Plating Type	Unplated
Prefilled Oxide Inhibitor	N
Sub Brand	HYSPLICE
Trade Name	HYSPLICE™
Type	YCS
UPC	781810014172
UPC 12 Digit	7818100141722

Dimensions

Dimension - B Length fraction	1-8/17 in
Dimension - B Length inch	1.47 in
Dimension - Inside Diameter inch	0.41 in
Dimension - L Length Overall mm	78 mm
Dimension - Length Overall inch	3.09 in
Dimension - Outside Diameter inch	0.63 in

Conductor Related

Conductor - Copper Str Size	1/0
Conductor - Copper Str Size Range	1/0
Conductor Type	<ul style="list-style-type: none"> • CU C Str-Size • CU C Solid-Size

Certifications and Compliance

Certification - CSA Approved	No
------------------------------	----

Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	CM
UL Listed	No

Logistics

Minimum Pack Quantity	1
-----------------------	---

For further technical assistance, please contact us

BURNDY Headquarters

47 East Industrial Park Drive
Manchester, New Hampshire 03109

Customer Service Hours:

8 AM - 8 PM Eastern Monday-Friday
Emergency Service 24-hours/365 Days
Phone: 1-800-346-4175
1-603-647-5299 (International)