

YDS3K7

by Burndy
Catalog ID: YDS3K7

Prop 65 Notice

Full tension copper splice designed to exceed the rated breaking strength of 30 percentage high conductivity EHS copperweld and lower strength conductors, Conductor: 5/16 (7 #10) (3 #7)



Product Details

General

Connector Type	Splice
Die Index	167
Material	Copper
Physical Attribute - Number of Crimps Required	5
Plated	N
Plating Type	Unplated
Prefilled Oxide Inhibitor	N
Trade Name	HYSPLICE™
UPC	781810014530

Dimensions

Dimension - B Length fraction	1-17/25 in
Dimension - B Length inch	4.68 in
Dimension - L Length Overall mm	249 mm
Dimension - Length Overall inch	9.80 in
Dimension - Outside Diameter inch	0.79 in

Conductor Related

Conductor - CopperWeld Str Size	3#7; 5/16 (7 #10)
---------------------------------	-------------------

Certifications and Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	CM
UL Listed	No

Logistics

Minimum Pack Quantity	15
-----------------------	----

For further technical assistance, please contact us

BURNDY Headquarters

47 East Industrial Park Drive
Manchester, New Hampshire 03109

Customer Service Hours:

8 AM - 8 PM Eastern Monday-Friday
Emergency Service 24-hours/365 Days
Phone: 1-800-346-4175
1-603-647-5299 (International)