



BURNDY Catalog Number
UPC Number
Description
Status

YDS29
 7818100146466
 250 CU HYSPLICE TENSION
 Active

Web Use
 BURNDY Product Line

Dimensional

B Length (Fraction) 3-1/2
 Length (in) 7.47
 Height (in) 0.95
 Outside Diameter 0.95
 B Length (in) 3.54
 Pad Width (in) 0.95
 Length (Fraction) 7-1/2

General

Product Description Hysplice, 250 (7, 19, 37) Str. , 7-1/2 in L, Full Tension Sleeve for All Aluminum Compressed and Compact Conductors

Prefilled (Oxide Inhibitor) Y

Conductor(s)

Aluminum Coated Steel Size (Range) N/A
 Copper Solid Size (Range) N/A
 Galvanized Steel Size (Range) N/A
 Copperweld Solid Size (Range) N/A
 Copper Stranded (Range) 250 kcmil
 CopperWeld Stranded Size (Range) N/A

Physical

Type of Splice Full Tension Sleeve
 Index Number 169

Approvals / Certifications

UL Listed N
 CSA Certified N
 ROHS Compatible Compliant
 UL Recognized N
 CULUS N

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
 Monday - Friday
 Phone: 800-346-4175