

YDS312H

by Burndy
Catalog ID: YDS312H

Prop 65 Notice

Full-tension steel splice designed for galvanized steel guy, messenger and "static:" conductors. ANSI C119.4 Class 1 (Full Tension), Die index: 257



Product Details

General

Connector Type	Splice
Die Index	257
Material	Steel
Plated	N
Plating Type	Unplated
Prefilled Oxide Inhibitor	Y
Trade Name	HYSPLICE™
UPC	781810015926
UPC 12 Digit	7818100159266

Dimensions

Dimension - B Length fraction	5 in
Dimension - B Length inch	5 in
Dimension - L Length Overall mm	268 mm
Dimension - Length Overall inch	10.55 in
Dimension - Outside Diameter inch	0.66 in

Conductor Related

Conductor - AL Coated Steel Size	5/16 (7) in
Conductor - AL Coated Steel Size Range	5/16 (7) in
Conductor - Galvanized Steel Str Size	5/16 (7) in
Conductor - Galvanized Steel Str Size Range	5/16 (7) in
Conductor - Grade	HS
Conductor Type	<ul style="list-style-type: none"> • ACSR C Str-Size • AL C Str-Size

Certifications and Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	CM

UL Listed	No
-----------	----

Logistics

Minimum Pack Quantity	1
-----------------------	---

For further technical assistance, please contact us

BURNDY Headquarters

47 East Industrial Park Drive
Manchester, New Hampshire 03109

Customer Service Hours:

8 AM - 8 PM Eastern Monday-Friday
Emergency Service 24-hours/365 Days
Phone: 1-800-346-4175
1-603-647-5299 (International)