



BURNDY Catalog Number
UPC Number
Description
Status

YA26L2TC38
7818100181566
HYLUG-SKIVED-2/0STR-(2)3
Active

Web Use
BURNDY Product Line

Dimensional

Tongue Angle
Length (in)
Tongue Type
Barrell Style
Bolt Hole Size (in)
Barrel Type
Thickness
B Length (in)
Pad Width (in)
E - in
Strip Length

Straight
3.20
Standard
Chamfered
0.39
Standard
0.12
0.94
0.83
1.00
1

General

Number of Holes

Product Description

2
Copper Compression lug, 2 Hole
w/ Inspection Window, 2/0 AWG,
3/8" Stud, 1" Stud Hole Spacing,
Short Barrel, Tin Plated

Conductor(s)

Flex (Class G) Size - Range
Flex (Class H) Size - Range
Flex (Class I) Size - Range
Copper Solid Size (Range)
DLO Size (Range)
Copper Stranded (Range)

N/A
N/A
N/A
N/A
N/A
2/0 AWG

Physical

Type of Plating
Color Code
Plated (Yes or No)
Index Number
Product Material

Tin - Electro Plated
Black
Y
13
Copper

Approvals / Certifications

UL Listed
CSA Certified
ROHS Compatible
UL Recognized
CULUS
Industry Standards

Y
Y
Compliant
N
N
UL468A-468B

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
Monday - Friday
Phone: 800-346-4175