



BURNDY Catalog Number
UPC Number
Description
Status

YAV28L2NTCFX
7818100220855
CU HYLUG-4/0 FLEX-NEMA
Active

Web Use
BURNDY Product Line

Tongue Angle
Length (in)
Tongue Type
Barrell Style
Bolt Hole Size (in)
Barrel Type
Thickness
B Length (in)
Pad Width (in)
E - in
Strip Length

Dimensional

Straight
4.62
Standard
Chamfered,Skived
0.52
Standard
0.15
1.03
1.14
1.75
1-1/16

Number of Holes

Product Description

General

2
Copper Compression Lug, 2 Hole
w/ Inspection Window, 4/0 Flex,
1/2" Stud, 1-3/4" Stud Hole
Spacing, Short Barrel, Tin Plated

Flex (Class G) Size - Range
Flex (Class H) Size - Range
Flex (Class I) Size - Range
Copper Solid Size (Range)
DLO Size (Range)
Copper Stranded (Range)

Conductor(s)

4/0 AWG
4/0 AWG
4/0 AWG
N/A
4/0 (550/#24) DLO
4/0 AWG

Type of Plating
Bolt Hole Size
Color Code
Plated (Yes or No)
Index Number
Product Material

Physical

Tin
1/2
Purple
Y
15
Copper

UL Listed
CSA Certified
ROHS Compatible
UL Recognized
CULUS

Approvals / Certifications

Y
Y
Compliant
N
N

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
Manchester NH 03109

Hours: 8:00 AM - 5:00 PM

Monday - Friday

Phone: 800-346-4175