



BURNDY Catalog Number
UPC Number
Description
Status

YAV6CL2TC14FX
7818100223755
CUHYLUG 6STRFLEX (2)1/4
Active

Web Use
BURNDY Product Line

Dimensional

Tongue Angle
Length (in)
Tongue Type
Barrell Style
Bolt Hole Size (in)
Barrel Type
Thickness
B Length (in)
Pad Width (in)
E - in
Strip Length

Straight
2.06
Standard
Chamfered
0.27
Standard
0.08
0.50
0.48
0.63
9/16

General

Number of Holes

Product Description

2
Copper Compression Lug, 2 Hole
w/ Inspection Window, 6 Flex,
1/4" Stud, 5/8" Stud Hole
Spacing, Short Barrel, Tin Plated

Conductor(s)

Flex (Class G) Size - Range
Flex (Class H) Size - Range
Flex (Class I) Size - Range
Copper Solid Size (Range)
DLO Size (Range)
Copper Stranded (Range)

6 AWG
6 AWG
6 AWG
6 AWG
6 (61/#24) DLO
6 AWG

Physical

Type of Plating
Bolt Hole Size
Color Code
Plated (Yes or No)
Index Number
Product Material

Tin - Electro Plated
1/4
Blue
Y
7
Copper

Approvals / Certifications

UL Listed
CSA Certified
ROHS Compatible
UL Recognized
CULUS

Y
Y
Compliant
N
N

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
Monday - Friday
Phone: 800-346-4175