

BURNDY Catalog Number
UPC Number
Description
Status


KVS26
 7818100612066
 2/0R-2/0T CU 2BLT CONN
 Active

Web Use
 BURNDY Product Line

General

Product Description

Compact, two-piece, high strength, high copper alloy BURNDY OKLIP recommended for heavy duty connections. Neoprene rings hold DURUM bolts in place during installation. Installed with ordinary wrench. Recommended tightening torque: 180 in-lb



Conductor(s)

Aluminum Run Size (Range) N/A
 Copper Tap Range 6 AWG-2/0 AWG
 CopperWeld Solid Run Size (Range) 3/0
 Copper Stranded Run (Range) 1 AWG-2/0 AWG
 CopperWeld Stranded Tap Size (Range) 3#12-7#8
 CopperWeld Solid Tap Size (Range) 3/0
 Aluminum Tap Size (Range) N/A
 Galvanized Steel Size (Range) N/A
 CopperWeld Stranded Run Size (Range) 3#7-7#8

Approvals / Certifications

UL Listed Y
 CSA Certified Y
 ROHS Compatible Exempt
 UL Recognized N
 CULUS N
 Industry Standards RUS

Physical

Installation Torque 180
 Type of Plating Unplated
 Plated (Yes or No) N
 Product Material Copper

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
 Monday - Friday
 Phone: 800-346-4175