



BURNDY Catalog Number
UPC Number
Description
Status


KVS28
 7818100623577
 4/0R-4/0T CU 2BLT CONN
 Active

Web Use
 BURNDY Product Line

General

Product Description

Compact, two-piece, high strength, high copper alloy BURNDY OKLIP recommended for heavy duty connections. Neoprene rings hold DURUM bolts in place during installation. Installed with ordinary wrench. Recommended tightening torque: 250 in-lb



Conductor(s)

Aluminum Run Size (Range) N/A
 Copper Tap Range 10 AWG-4/0 AWG
 CopperWeld Solid Run Size (Range) 4/0
 Copper Stranded Run (Range) 1/0 -4/0 AWG
 CopperWeld Stranded Tap Size (Range) 3#12-7#6
 CopperWeld Solid Tap Size (Range) 4/0
 Aluminum Tap Size (Range) N/A
 Galvanized Steel Size (Range) N/A
 CopperWeld Stranded Run Size (Range) 7#8-7#6

Approvals / Certifications

UL Listed Y
 CSA Certified Y
 ROHS Compatible Compliant
 UL Recognized N
 CULUS N
 Industry Standards RUS

Physical

Installation Torque 250
 Type of Plating Unplated
 Plated (Yes or No) N
 Product Material Copper

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
 Monday - Friday
 Phone: 800-346-4175