

BURNDY Catalog Number
UPC Number
Description
Status


KVS34
 7818100632000
 500R-500T CU 2BLT CONN
 Active

Web Use
 BURNDY Product Line

General

Product Description

Compact, two-piece, high strength, high copper alloy BURNDY OKLIP recommended for heavy duty connections. Neoprene rings hold DURIUM bolts in place during installation. Installed with ordinary wrench. Recommended tightening torque: 375 in-lb



Conductor(s)

Aluminum Run Size (Range) N/A
 Copper Tap Range 10 AWG-500 kcmil
 CopperWeld Solid Run Size (Range) N/A
 Copper Stranded Run (Range) 400 kcmil-500 kcmil
 CopperWeld Stranded Tap Size (Range) 3#12-19#6
 CopperWeld Solid Tap Size (Range) N/A
 Aluminum Tap Size (Range) N/A
 Galvanized Steel Size (Range) N/A
 CopperWeld Stranded Run Size (Range) 19#6

Approvals / Certifications

UL Listed Y
 CSA Certified Y
 ROHS Compatible Compliant
 UL Recognized N
 CULUS N
 Industry Standards UL486C

Physical

Installation Torque 375
 Type of Plating Unplated
 Plated (Yes or No) N
 Product Material Copper

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
 Monday - Friday
 Phone: 800-346-4175