



BURNDY Catalog Number
UPC Number

KVSW28
 7818100665533
 4/0R-4/0T CU 2BLT CONN,2.50 IN
 H
 Active

Description
Status

Web Use
 BURNDY Product Line

Product Description

General

Mechanical Connector For
 CUWeld and Copper Supplied with
 a CU alloy Spacer that seperates
 run and tap conductors,
 Recommended Torque: 250 LBS

Conductor(s)

Aluminum Run Size (Range) N/A
 Copper Tap Range 6 AWG-4/0 AWG
 CopperWeld Solid Run Size (Range) N/A
 Copper Stranded Run (Range) 1/0 -4/0 AWG
 CopperWeld Stranded Tap Size (Range) N/A
 CopperWeld Solid Tap Size (Range) N/A
 Aluminum Tap Size (Range) N/A
 Galvanized Steel Size (Range) N/A
 CopperWeld Stranded Run Size (Range) N/A

Approvals / Certifications

UL Listed N
 CSA Certified N
 ROHS Compatible Exempt
 UL Recognized N
 CULUS N

Physical

Installation Torque 240
 Type of Plating Unplated
 Plated (Yes or No) N
 Product Material Copper

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
 Monday - Friday
 Phone: 800-346-4175