


[On Line Catalog](#)


BURNDY Catalog Number
UPC Number
Description
Status

KVS31
 7818100668055
 CU OKLIP 250-350, 4SOL-3
 Active

Web Use
 BURNDY Product Line

Dimensional

Width (in) 2.25
 Length (in) 1.62
 Height (in) 2.80

General

Mechanical Connector For
 CUWeld and Copper Supplied with
 a CU alloy Spacer that separates
 run and tap conductors,
 Recommended Torque: 325 LBS

Product Description

Conductor(s)

Aluminum Run Size (Range) N/A
 Copper Tap Range 4 AWG-350 kcmil
 CopperWeld Solid Run Size (Range) N/A
 Copper Stranded Run (Range) 250 kcmil-350 kcmil
 CopperWeld Stranded Tap Size (Range) N/A
 CopperWeld Solid Tap Size (Range) N/A
 Aluminum Tap Size (Range) N/A
 Galvanized Steel Size (Range) N/A
 CopperWeld Stranded Run Size (Range) N/A

Physical

Installation Torque 480
 Type of Plating Unplated
 Plated (Yes or No) N
 Product Material Copper

Approvals / Certifications

UL Listed N
 CSA Certified N
 ROHS Compatible Exempt
 UL Recognized N
 CULUS N

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
 Monday - Friday
 Phone: 800-346-4175