


**BURNDY Catalog Number**  
**UPC Number**  
**Description**  
**Status**

KVSW34  
 7818100673077  
 CU OKLIP 400-500, 4STR-5  
 Active

**Web Use**  
 BURNDY Product Line



General	
Product Description	Mechanical Connector For CUWeld and Copper Supplied with a CU alloy Spacer that separates run and tap conductors, Recommended Torque: 375 LBS
Conductor(s)	
Aluminum Run Size (Range)	N/A
Copper Tap Range	4 AWG-500 kcmil
CopperWeld Solid Run Size (Range)	N/A
Copper Stranded Run (Range)	400 kcmil-500 kcmil
CopperWeld Stranded Tap Size (Range)	N/A
CopperWeld Solid Tap Size (Range)	N/A
Aluminum Tap Size (Range)	N/A
Galvanized Steel Size (Range)	N/A
CopperWeld Stranded Run Size (Range)	N/A
Approvals / Certifications	
UL Listed	N
CSA Certified	N
ROHS Compatible	Exempt
UL Recognized	N
CULUS	N
Physical	
Installation Torque	480
Type of Plating	Unplated
Plated (Yes or No)	N
Product Material	Copper
Documentation	

For further technical assistance, please contact us

**BURNDY LLC - USA**

47 East Industrial Park Drive  
 Manchester NH 03109

**BURNDY Technical Services**

47 East Industrial Park Drive  
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM  
 Monday - Friday  
 Phone: 800-346-4175