


[On Line Catalog](#)


**BURNDY Catalog Number**  
**UPC Number**  
**Description**  
**Status**

KVS40  
 7818100678022  
 CU OKLIP 400-800, 4/0 -  
 Active

**Web Use**  
 BURNDY Product Line

**Dimensional**

Width (in) 2.72  
 Length (in) 2.31  
 Height (in) 3.47

**General**

Mechanical Connector For  
 CUWeld and Copper Supplied with  
 a CU alloy Spacer that separates  
 run and tap conductors,  
 Recommended Torque: 500 LBS

**Product Description**

**Conductor(s)**

Aluminum Run Size (Range) N/A  
 Copper Tap Range 4/0 AWG-800 kcmil  
 CopperWeld Solid Run Size (Range) N/A  
 Copper Stranded Run (Range) 400 kcmil-800 kcmil  
 CopperWeld Stranded Tap Size (Range) N/A  
 CopperWeld Solid Tap Size (Range) N/A  
 Aluminum Tap Size (Range) N/A  
 Galvanized Steel Size (Range) N/A  
 CopperWeld Stranded Run Size (Range) N/A

**Physical**

Installation Torque 480  
 Type of Plating Unplated  
 Plated (Yes or No) N  
 Product Material Copper

**Approvals / Certifications**

UL Listed N  
 CSA Certified N  
 ROHS Compatible Exempt  
 UL Recognized N  
 CULUS N

**Documentation**

**For further technical assistance, please contact us**

**BURNDY LLC - USA**

47 East Industrial Park Drive  
 Manchester NH 03109

**BURNDY Technical Services**

47 East Industrial Park Drive  
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM  
 Monday - Friday  
 Phone: 800-346-4175