




**BURNDY Catalog Number**  
**UPC Number**  
**Description**  
**Status**

KVSU26  
 7818100811055  
 UNIV OKLIP 2-2/0/6-2/0  
 Active

**Web Use**  
 BURNDY Product Line



**General**

Product Description

Tin-plated copper alloy connector with tin plated silicon bronze hardware. Spacer bar separates dissimilar conductors and provides long contact length, Tightening torque: 180 in -lb, wrench size: 1/2 cross flats

**Conductor(s)**

Aluminum Run Size (Range) 2 AWG-2/0 AWG  
 Copper Tap Range 6 AWG-2/0 AWG  
 CopperWeld Solid Run Size (Range) #1 - 3/0  
 Copper Stranded Run (Range) 2 AWG-2/0 AWG  
 CopperWeld Stranded Tap Size (Range) #6 - 3/0  
 CopperWeld Solid Tap Size (Range) #6 - 3/0  
 Aluminum Tap Size (Range) 6 AWG-2/0 AWG  
 Galvanized Steel Size (Range) 5/16 (7) in-7/16 (7) in  
 CopperWeld Stranded Run Size (Range) #1 - 3/0

**Approvals / Certifications**

UL Listed N  
 CSA Certified Y  
 ROHS Compatible Exempt  
 UL Recognized N  
 CULUS N

**Physical**

Installation Torque 180  
 Type of Plating Tin  
 Plated (Yes or No) Y  
 Product Material Copper Alloy

**Documentation**

For further technical assistance, please contact us

**BURNDY LLC - USA**

47 East Industrial Park Drive  
 Manchester NH 03109

**BURNDY Technical Services**

47 East Industrial Park Drive  
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM  
 Monday - Friday  
 Phone: 800-346-4175