



Color: Ivory

UPC Code: 07847781857



8200-l

Item Description

Duplex Receptacle Outlet, Extra Heavy-Duty Hospital Grade, Smooth Face, 15 Amp, 125 Volt, Back or Side Wire, NEMA 5-15R, 2-Pole, 3-Wire, Self-Grounding - Ivory

Technical Information

AC Horsepower Ratings Horsepower Rating: 1/2 HP

Electrical Specifications

Amperage: 15 A Current Limiting: Full Rated Current Dielectric Voltage: Withstands 2000V per UL498

Grounding: Self-Grounding **Pole:** 2

Temperature Rise: Max 30C after 250 cycles OL at 200 percent rated current Voltage: 125 VAC

Wire: 3

Environmental Specifications Flammability: Rated V-2 per UL 94 Operating Temperature: -40°C to 60°C

Material Specifications

Body Material: Nylon Clamp Nuts: Zinc-Plated Steel

Color: Ivory

Face Material: Nylon

Ground Clips: Nickel-Plated Brass Grounding Screw: Plated Brass

Line Contacts: Nickel-Plated Brass Triple-Wipe .040 Thick

Strap Material: Nickel-Plated Brass Terminal Screws: Nickel-Plated Brass 10-32 Mechanical Specifications **Product ID:** Markings are permanently

marked on device Terminal Accom.: 14-10 AWG Terminal ID: Brass-Hot, Green-Ground,

Silver-Neutral Termination: Back or Side Wire

Torque Range: 14-16 inch pounds


Product Features


Color: Ivory Device Type: Duplex Receptacle Outlet Grade: Extra Heavy-Duty Hospital Grade

NEMA: 5-15R Feature 4: Smooth Face

Standards and Certifications

ANSI: C-73 CSA C22.2 No. 42: File 152105 NEMA: WD-6 NOM: 057 RoHS: Non-Compliant UL498HG: File E13399 UL Fed Spec WC-596: File E13399 Warranty: 10-Year Limited





5-15R

SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:	
JOB NUMBER:		

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

Teléfono: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2018 Leviton Manufacturing Co., Inc. Todos los derechos reservados. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/

