



YSU25R4W

by Burndy Catalog ID: YSU25R4W

Prop 65 Notice

Heavy-walled AL tubing with solid barrier minimizes galvanic corrosion, Color Code: Yellow (Side A), Blue (Side B)

Product Details

General

Color Code - Side A	Yellow
Color Code - Side B	Blue
Die Index	243;BG or 5/8
Material	Aluminum
Plated	Y
Plating Type	Tin - Hot Dipped
Prefilled Oxide Inhibitor	Y
Trade Name	LINKIT™
Туре	Service Entrance, Uninsulated, Center Stop
UPC	781810143582
UPC 12 Digit	7818101435822

Dimensions

Dimension - B Length inch	0.87 in
Dimension - L Length Overall mm	51 mm
Dimension - Length Overall inch	2 in
Dimension - Outside Diameter inch	0.65 in

Conductor Related

Conductor - ACSR Str Size A	1/0 (6/1) Raven AWG
Conductor - ACSR Str Size B	6 (6/1) Turkey AWG
Conductor - AL Str Size A	1/0 AWG
Conductor - AL Str Size B	5 AWG, 6 AWG
Conductor - AL Str Size B Range	5 AWG- 6 AWG
Conductor - Copper Solid Size B	4 AWG
Conductor - Copper Str Size A	1/0 AWG
Conductor - Copper Str Size B	5 AWG, 6 AWG
Conductor - Copper Str Size B Range	5 AWG- 6 AWG

Certifications and Compliance

Certification - CSA Approved	No
Certification - ETL	No

Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	СМ
UL Listed	No

Logistics

Minimum Pack Quantity	100	

For further technical assistance, please contact us

BURNDY Headquarters

47 East Industrial Park Drive Manchester, New Hampshire 03109

Customer Service Hours:

8 AM - 8 PM Eastern Monday-Friday Emergency Service 24-hours/365 Days

Phone: 1-800-346-4175

1-603-647-5299 (International)