



YSD27R2W

by Burndy Catalog ID: YSD27R2W

Prop 65 Notice

AL compression sleeve with solid center barrier, Designed for commercial and heavy residential services, Color Code: Black (Side A), Orange (Side B)

Product Details

General

| Color Code - Side A | Black |
|---------------------------|-------------------------------|
| Color Code - Side B | Orange |
| Die Index | 249;K-840 |
| Material | Aluminum |
| Plated | Y |
| Plating Type | Tin - Hot Dipped |
| Prefilled Oxide Inhibitor | Y |
| Trade Name | LINKIT™ |
| Туре | Service Entrance, Uninsulated |
| UPC | 781810145050 |
| UPC 12 Digit | 7818101450500 |

Dimensions

| Dimension - L Length Overall mm | 102 mm |
|-----------------------------------|----------|
| Dimension - Length Overall inch | 4 in |
| Dimension - Outside Diameter inch | .3125 in |

Conductor Related

| Conductor - ACSR Str Size A | 3/0 AWG |
|-------------------------------------|--------------------------------------|
| Conductor - ACSR Str Size B | 4 (6/1) Swan AWG;4 (7/1) Swanate AWG |
| Conductor - ACSR Str Size B Range | 4 (6/1) Swan AWG-4 (7/1) Swanate AWG |
| Conductor - AL Str Size A | 3/0 AWG |
| Conductor - AL Str Size B | 4 AWG;3 AWG;2 AWG |
| Conductor - AL Str Size B Range | 4 AWG-2 AWG |
| Conductor - Copper Str Size A | 3/0 AWG |
| Conductor - Copper Str Size B | 4 AWG;3 AWG;2 AWG |
| Conductor - Copper Str Size B Range | 4 AWG-2 AWG |

Certifications and Compliance

| Certification - CSA Approved | No |
|------------------------------|----|
| Certification - ETL | No |

| Certification - UL Recognized | No |
|------------------------------------|----|
| Certification - cULus | No |
| Standards - RoHS Compliance Status | СМ |
| UL Listed | No |

Logistics

| ım Pack Quantity | 25 | |
|------------------|----|--|
|------------------|----|--|

For further technical assistance, please contact us

BURNDY Headquarters

47 East Industrial Park Drive Manchester, New Hampshire 03109

Customer Service Hours:

8 AM - 8 PM Eastern Monday-Friday Emergency Service 24-hours/365 Days

Phone: 1-800-346-4175

1-603-647-5299 (International)