



**BURNDY Catalog Number**  
**UPC Number**  
**Description**  
**Status**

YCB2R  
 7818101515011  
 2 AL STIRRUP W/ SPLICE  
 Active

**Web Use**  
 BURNDY Product Line

Length (in)  
 Bail Size  
 Height (in)  
 D or Diameter (Fraction) (in)  
 F - Spacing (in) (Width - Center to Center)  
 D - in  
 Length (Fraction)

**Dimensional**

9  
 1/0  
 3.75  
 2-1/2  
 2.50  
 2.50  
 9

**General**

Permanent compression hot-line clamp adapter with aluminum run and copper bail. Permits hot-line tapping without arcing or chafing damage to aluminum conductor, Aluminum: 2 Str. - 6 Sol.

**Product Description**

Prefilled (Oxide Inhibitor)

AAAC 5005-Size (Range)  
 ACSR Size (Range)  
 ACSR Compact Size (Range)  
 AAAC 6201 Size (Range)  
 Aluminum Size (Range)

**Conductor(s)**

N  
 48.69 (7) kcmil-77.47 (7) kcmil  
 4 (6/1) Swan AWG-2 (7/1) Sparate AWG  
 4 AWG-2 AWG  
 48.69 (7) kcmil-77.47 (7) kcmil  
 6 AWG-2 AWG

Type of Plating  
 Plated (Yes or No)  
 Index Number  
 Product Material

**Physical**

Unplated  
 N  
 BG  
 Aluminum

**Approvals / Certifications**

UL Listed  
 CSA Certified  
 ROHS Compatible  
 UL Recognized  
 CULUS

N  
 N  
 Compliant  
 N  
 N

**Documentation**

For further technical assistance, please contact us

**BURNDY LLC - USA**

47 East Industrial Park Drive  
 Manchester NH 03109

**BURNDY Technical Services**

47 East Industrial Park Drive  
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM  
 Monday - Friday  
 Phone: 800-346-4175