



BURNDY Catalog Number
UPC Number
Description
Status

KSA350
 7818101835266
 TRITAP SERVIT 350-4STR
 Active

Web Use
 BURNDY Product Line

Dimensional

Width (in)	1.50
Height (in)	1.50
Size (Hex) or Size (Bolt)	1-3/8
Cross Flats	1.69
Size (Hex) or Size (Bolt) - in	1.38
B Length (in)	2.18
Bolt Diameter (in)	1.50
Min Tap Size with Max Run Size	350 kcmil (.681) - #4 Str. (.232)
Max Tap size with Max Run Size	350 kcmil (.681) - 350 kcmil (.681)
Min Tap Size with Min Run Size	#1/0 Str. Compact (.336) - #4 Str. (.232)
B Length (Fraction)	2-1/6

General

Product Description

Aluminum Split Bolt, (Run, Tap)::
 Al-Al: 350 kcmil, 350 kcmil, Al-Cu: 1/0 AWG (Str), 4 AWG (Str), Cu-Cu: 350 kcmil, 4 AWG (Str), Tin Plated

Conductor(s)

Aluminum Run Size (Range)	1/0 AWG-350 kcmil
Copper Tap Range	4 AWG-350 kcmil
Copper Stranded Run (Range)	1/0 -350 kcmil
Copper Solid Tap (Range)	8 AWG-2 AWG
Aluminum Tap Size (Range)	4 AWG-350 kcmil

Physical

Installation Torque	650
Type of Plating	Tin
Plated (Yes or No)	Y
Product Material	Aluminum

Approvals / Certifications

Rated for Direct Burial	N
UL Listed	Y
CSA Certified	Y
ROHS Compatible	Compliant
UL Recognized	N
CULUS	N
Industry Standards	UL468A-468B

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
 Monday - Friday
 Phone: 800-346-4175