



BURNDY Catalog Number
UPC Number
Description
Status

YGHC34C29
 7818102210755
 300-500 TO 3/0-250 GRD C
 Active

Web Use
 BURNDY Product Line

B Length (in)
 Diameter (in) - Total

Dimensional
 0.88
 2.67

Product Description

General
 Copper Compression C Connector,
 300-500 kcmil (Run) & 3/0
 AWG(Str) - 250 kcmil (Tap)

Copper Tap Range
 Copper Stranded Run (Range)
 Rod Size Run (Range)
 Copper Solid Tap (Range)
 Rebar Run Size (Range)
 Copper Solid Run Size (Range)

Conductor(s)
 3/0 AWG-250 kcmil
 300 kcmil-500 kcmil
 3/8 in
 N/A
 N/A
 N/A

Type of Plating
 Connector Type
 Plated (Yes or No)
 Index Number
 Product Material

Physical
 Unplated
 Tap
 N
 1011
 Copper

Rated for Direct Burial
 UL Listed
 CSA Certified
 ROHS Compatible
 UL Recognized
 CULUS
 Industry Standards

Approvals / Certifications
 Y
 Y
 Y
 Compliant
 N
 N
 UL468A-468B,UL467,IEEE 837

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
 Monday - Friday
 Phone: 800-346-4175