



BURNDY Catalog Number
UPC Number
Description
Status

AMS250
7818102410355
250-6 DUAL RATED SPLICE
Active

Web Use
BURNDY Product Line

Width (in)
Length (in)
Hex Size
H1

Dimensional

1.00
4.09
5/16
1.09

Number of Screws

General

4
Aluminum Mechanical Splice, 250
kcmil-6 AWG, 5/8" Screw Dia, 4
Screws, 5/16" Hex Size, Al/Cu
Rated, Tin Plated

Product Description

Conductor(s)

Aluminum Size (Range)
Copper Solid Size (Range)
Copper Stranded (Range)

6 AWG-4/0 AWG
4 AWG-4/0 AWG
6 AWG-250 kcmil

Installation Torque
Type of Plating
Connector Type
Plated (Yes or No)
Product Material

Physical

50
Tin
Splice, Reducer
Y
Aluminum

Approvals / Certifications

Rated for Direct Burial
UL Listed
CSA Certified
ROHS Compatible
Industry Standards

N
Y
Y
Exempt
UL467

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
Monday - Friday
Phone: 800-346-4175