



BURNDY Catalog Number	AMS350
UPC Number	7818102410422
Description	350-6 DUAL RATED SPLICE
Status	Active

Web Use
BURNDY Product Line

	Dimensional
Width (in)	1.00
Length (in)	4.34
Hex Size	5/16
H1	1.09
	General
Number of Screws	4
Product Description	Aluminum Mechanical Splice, 350 kcmil-6 AWG, 11/16" Screw Dia, 4 Screws, 5/16" Hex Size, Al/Cu Rated, Tin Plated
	Conductor(s)
Aluminum Size (Range)	6 AWG-350 kcmil
Copper Solid Size (Range)	4 AWG-4/0 AWG
Copper Stranded (Range)	6 AWG-350 kcmil
	Physical
Installation Torque	275
Type of Plating	Tin
Connector Type	Splice, Reducer
Plated (Yes or No)	Y
Product Material	Aluminum
	Approvals / Certifications
Rated for Direct Burial	N
UL Listed	Y
CSA Certified	Y
ROHS Compatible	Exempt
Industry Standards	UL467
Documentation	

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
Monday - Friday
Phone: 800-346-4175