

BURNDY Catalog Number
UPC Number
Description
Status

AMS500
 7818102410599
 500-3/0 DUAL RATED SPLIC
 Active

Web Use
 BURNDY Product Line

Width (in)
 Length (in)
 Hex Size
 H1

Dimensional

1.25
 4.78
 3/8
 1.38


Number of Screws

General

4

Product Description

Aluminum Mechanical Splice, 500
 kcmil-3/0 AWG, 13/16" Screw Dia,
 4 Screws, 3/8" Hex Size, Al/Cu
 Rated, Tin Plated



Aluminum Size (Range)
 Copper Solid Size (Range)
 Copper Stranded (Range)

Conductor(s)

3/0 AWG-500 kcmil
 3/0 AWG-4/0 AWG
 3/0 AWG-500 kcmil

Installation Torque
 Type of Plating
 Connector Type
 Plated (Yes or No)
 Product Material

Physical

375
 Tin
 Splice, Reducer
 Y
 Aluminum

Approvals / Certifications

Rated for Direct Burial
 UL Listed
 CSA Certified
 ROHS Compatible
 Industry Standards

N
 Y
 Y
 Exempt
 UL467

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
 Monday - Friday
 Phone: 800-346-4175