




**BURNDY Catalog Number**  
**UPC Number**  
**Description**  
**Status**

AMS750  
 7818102410666  
 750-250 DUAL RATED SPLIC  
 Active

**Web Use**  
 BURNDY Product Line



Dimensional	
Width (in)	1.44
Length (in)	6.06
Hex Size	1/2
H1	1.63
General	
Number of Screws	4
Product Description	Aluminum Mechanical Splice, 750-250 kcmil, 15/16" Screw Dia, 4 Screws, 1/2" Hex Size, Al/Cu Rated, Tin Plated
Conductor(s)	
Aluminum Size (Range)	250 kcmil-750 kcmil
Copper Solid Size (Range)	N/A
Copper Stranded (Range)	250 kcmil-750 kcmil
Physical	
Installation Torque	500
Type of Plating	Tin
Connector Type	Splice, Reducer
Plated (Yes or No)	Y
Product Material	Aluminum
Approvals / Certifications	
Rated for Direct Burial	N
UL Listed	Y
CSA Certified	Y
ROHS Compatible	Exempt
UL Recognized	N
CULUS	N
Industry Standards	UL467
Documentation	

For further technical assistance, please contact us

**BURNDY LLC - USA**

47 East Industrial Park Drive  
 Manchester NH 03109

**BURNDY Technical Services**

47 East Industrial Park Drive  
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM  
 Monday - Friday  
 Phone: 800-346-4175