



BURNDY Catalog Number
UPC Number
Description
Status

K11A34U2
 7818103702788
 TWO: 4/0 STR - 500 DUAL
 Active

Web Use
 BURNDY Product Line

Dimensional	
Width (in)	1.44
Length (in)	2.91
Height (in)	2.40
Thickness	0.63
D - in	2.31
Stud Size (Fraction)	1/4
E - in	0.69
N (in)	0.25
General	
Number of Conductors	2
Number of Holes	2
Product Description	Aluminum Universal Terminal, 2 Hole, Two: 4/0 AWG (Str)-500 kcmil, 1/4" Stud, .69" Stud Hole Spacing, 2 Screws, Al/Cu Rated, Tin Plated
Conductor(s)	
Aluminum Size (Range)	4/0 AWG-500 kcmil
Copper Solid Size (Range)	4/0 AWG
Copper Stranded (Range)	4/0 AWG-500 kcmil
Physical	
Installation Torque	375
Type of Plating	Tin
Connector Type	Terminal
Plated (Yes or No)	Y
Product Material	Aluminum
Approvals / Certifications	
Rated for Direct Burial	N
UL Listed	Y
CSA Certified	Y
ROHS Compatible	Exempt
UL Recognized	N
CULUS	N
Industry Standards	UL468A-468B
Documentation	

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
 Monday - Friday
 Phone: 800-346-4175