



Color: White

UPC Code: 07847783076 Country Of Origin: Mexico

NEMA: 5-20R



21254-W

Brand Features

Leviton's line of Heavy-Duty Industrial Grade receptacles are available with a number of wiring options and features. The beauty, durability and versatility of Decora® devices and surge supression receptacles are perfect for a variety of industrial applications.

Item Description

20 Amp, 125 Volt, NEMA 5-20R, 2P, 3W, Industrial Series Extra Heavy Duty Specification Grade, 4-In-1 Receptacle, Straight Blade, Grounding, Steel Strap, -WHITE

Technical Information

AC Horsepower Ratings At Rated Voltage: 1 HP

Electrical Specifications Amperage: 20 A

Current Limiting: Full Rated Current Dielectric Voltage: Withstands 2000V

per UL498

Grounding: Grounding

Pole: 2

Temperature Rise: Max 30C after 50 cycles OL at 150 percent rated current

Voltage: 125 VAC

Wire: 3

Environmental Specifications Flammability: Rated V-2 per UL 94 Operating Temperature: -40°C to 60°C

Material Specifications Body Material: Nylon

Color: White

Cover Material: Nylon

Grounding Screw: Plated Steel Line Contacts: Phosphor Bronze **Strap Material:** Galvanized Steel with Riveted Ground Contacts

Terminal Screws: Plated Brass

Mechanical Specifications

Product ID: Ratings are permanently

marked on device

Terminal Accom.: 14-12 AWG

Terminal ID: Brass-Hot, Green-Ground,

Silver-Neutral

Termination: Side Wire

Torque Range: 12-14 inch pounds

Product Features Brand: 4-in-1 Color: White

Device Type: Quadruplex Receptacle

Outlet

Grade: Heavy-Duty Industrial Specification Grade

NEMA: 5-20R

Standards and Certifications

ANSI: C-73


CSA C22.2 No. 42: File 152105

NEMA: WD-1 WD-6


NOM: 057

UL498: File E13399 Warranty: 5 Year Limited

Dimensional Diagram



Wiring Diagram



5-20R

SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:
JOB NUMBER:	

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

 $\label{eq:temperature} \textbf{Teléfono: +1-800-323-8920} \cdot \textbf{FAX: +1-800-832-9538} \cdot \textbf{Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005}$

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

 $\ \odot$ 2018 Leviton Manufacturing Co., Inc. Todos los derechos reservados. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/

