



BURNDY Catalog Number
UPC Number
Description
Status

KA40U
 7818103703088
 300-800 DUAL RATED
 Active

Web Use
 BURNDY Product Line

Dimensional

Width (in) 1.75
 Length (in) 3.50
 Bolt Hole Size (in) 0.62
 Thickness 0.50
 D - in 1.85
 Pad Width (in) 1.77
 N (in) 0.81

General

Number of Conductors 1
 Number of Holes 1
 Product Description Aluminum Universal Terminal, 1 Hole, 300-800 kcmil, 1/2" Stud, 1 Screw, Al/Cu Rated, Tin Plated

Conductor(s)

Aluminum Size (Range) 300 - 800 kcmil
 Copper Solid Size (Range) N/A
 Copper Stranded (Range) 300 kcmil-800 kcmil

Physical

Installation Torque 550
 Type of Plating Tin
 Connector Type Terminal
 Bolt Hole Size 5/8
 Plated (Yes or No) Y
 Product Material Aluminum

Approvals / Certifications

Rated for Direct Burial N
 UL Listed Y
 CSA Certified Y
 ROHS Compatible Exempt
 Industry Standards UL468A-468B

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
 Monday - Friday
 Phone: 800-346-4175