



BURNDY Catalog Number
UPC Number
Description
Status

YA31L2TC38
 7818105036833
 CU HYDENT 350 MCM(2) 3/8
 Active

Web Use
 BURNDY Product Line

Dimensional

Tongue Angle Straight
 Length (in) 3.51
 Tongue Type Standard
 Barrell Style Chamfered
 Bolt Hole Size (in) 0.39
 Barrel Type Standard
 Thickness 0.18
 B Length (in) 1.06
 Pad Width (in) 1.29
 E - in 1.00
 Strip Length 1-1/8

General

Number of Holes 2
 Product Description Copper Compression Lug, 2 Hole w/ Inspection Window, 350 kcmil, 3/8" Stud, 1" Stud Hole Spacing, Short Barrel, Tin - Electro Plated

Conductor(s)

Flex (Class G) Size - Range N/A
 Flex (Class H) Size - Range N/A
 Flex (Class I) Size - Range N/A
 Copper Solid Size (Range) N/A
 DLO Size (Range) N/A
 Copper Stranded (Range) 350 kcmil

Physical

Type of Plating Tin - Electro Plated
 Color Code Red
 Plated (Yes or No) Y
 Index Number 18,324
 Product Material Copper

Approvals / Certifications

UL Listed Y
 CSA Certified Y
 ROHS Compatible Compliant
 UL Recognized N
 CULUS N
 Industry Standards UL468A-468B

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
 Monday - Friday
 Phone: 800-346-4175