



BURNDY Catalog Number
UPC Number
Description
Status

YA30L
 7818105048577
 300 CU 1-HOLE SHORT 1/2
 Active

Web Use
 BURNDY Product Line

Dimensional

Tongue Angle	Straight
Length (in)	2.69
Tongue Type	Standard
Barrell Style	Chamfered,Skived
Bolt Hole Size (in)	0.52
Barrel Type	Standard
Thickness	0.16
B Length (in)	1.03
Pad Width (in)	1.20
Strip Length	1-1/16

General

Number of Holes	1
Product Description	CU Compression Terminal Code Conductor, Beveled Entry, 1 Hole/W/InspWindow, 300kcmil(Code) 300(Navy), 600V- 35kV, 1/2" Stud, Standard Barrel, Electro-Tin Plated

Conductor(s)

Flex (Class G) Size - Range	N/A
Flex (Class H) Size - Range	N/A
Flex (Class I) Size - Range	N/A
Copper Solid Size (Range)	N/A
DLO Size (Range)	N/A
Copper Stranded (Range)	300 kcmil

Physical

Type of Plating	Tin - Electro Plated
Color Code	White
Plated (Yes or No)	Y
Index Number	17
Product Material	Copper

Approvals / Certifications

UL Listed	Y
CSA Certified	Y
ROHS Compatible	Compliant
UL Recognized	N
CULUS	N
Industry Standards	UL467

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
 Monday - Friday
 Phone: 800-346-4175