



**BURNDY Catalog Number**  
**UPC Number**  
**Description**  
**Status**

YA4CL3BOX  
 781810524388  
 CULUG- 4 STR-SHORT-5/16  
 Active

**Web Use**  
 BURNDY Product Line

**Dimensional**

Tongue Angle	Straight
Length (in)	1.79
Tongue Type	Standard
Barrell Style	Chamfered,Skived
Bolt Hole Size (in)	0.33
Barrel Type	Standard
Thickness	0.08
B Length (in)	0.81
Pad Width (in)	0.50
Strip Length	7/8

**General**

Number of Holes	1
Product Description	CU Compression Terminal Code Conductor, Beveled Entry, 1 Hole/W/InspWindow, #4AWG(Code) 40(Navy), 600V- 35kV, 5/16" Stud, Standard Barrel, Electro-Tin Plated

**Conductor(s)**

Flex (Class G) Size - Range	N/A
Flex (Class H) Size - Range	N/A
Flex (Class I) Size - Range	N/A
Copper Solid Size (Range)	N/A
DLO Size (Range)	N/A
Copper Stranded (Range)	4 AWG

**Physical**

Type of Plating	Tin - Electro Plated
Bolt Hole Size	5/16
Color Code	Gray
Plated (Yes or No)	Y
Index Number	8
Product Material	Copper

**Approvals / Certifications**

UL Listed	Y
CSA Certified	Y
ROHS Compatible	Compliant
UL Recognized	N
CULUS	N

**Documentation**

For further technical assistance, please contact us

**BURNDY LLC - USA**

47 East Industrial Park Drive  
 Manchester NH 03109

**BURNDY Technical Services**

47 East Industrial Park Drive  
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM  
 Monday - Friday  
 Phone: 800-346-4175