



**BURNDY Catalog Number**  
**UPC Number**  
**Description**  
**Status**

K3A29U2N  
 7818106011055  
 THREE:6STR-250 DUAL RATE  
 Active

**Web Use**  
 BURNDY Product Line

**Dimensional**

Width (in)	2.81
Length (in)	4.00
Bolt Hole Size (in)	0.57
Thickness	0.31
D - in	3.16
Pad Width (in)	3.01
E - in	1.75
N (in)	0.63

**General**

Number of Conductors	3
Number of Holes	2
Product Description	Aluminum Universal Terminal, 3 Conductor, 2 Hole, 6 AWG (Str)-250 kcmil, 1/2" Stud, 1.75" Stud Hole Spacing, 3 Screws, Al/Cu Rated, Tin Plated

**Conductor(s)**

Aluminum Size (Range)	6 STR - 250 kcmil
Copper Solid Size (Range)	N/A
Copper Stranded (Range)	6 AWG-250 kcmil

**Physical**

Installation Torque	275
Type of Plating	Tin
Connector Type	Terminal
Bolt Hole Size	9/16
Plated (Yes or No)	Y
Product Material	Aluminum

**Approvals / Certifications**

Rated for Direct Burial	N
UL Listed	Y
CSA Certified	Y
ROHS Compatible	Exempt
Industry Standards	UL468A-468B

**Documentation**

For further technical assistance, please contact us

**BURNDY LLC - USA**

47 East Industrial Park Drive  
 Manchester NH 03109

**BURNDY Technical Services**

47 East Industrial Park Drive  
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM  
 Monday - Friday  
 Phone: 800-346-4175