

# YCS34

by Burndy  
Catalog ID: YCS34

CU loop splice connector designed to withstand jumper loop tensile and vibration stresses up to 60 percentage RBS, Index: 210



## Product Details

### General

Connector Type	Splice
Die Index	210
Material	Copper
Physical Attribute - Number of Crimps Required	2
Plated	N
Plating Type	Unplated
Prefilled Oxide Inhibitor	N
Trade Name	HYSPLICE™
UPC	781810820605

### Dimensions

Dimension - A Outside Diameter inch	1.38 in
Dimension - B Length fraction	2-1/2 in
Dimension - B Length inch	2.5 in
Dimension - B Outside Diameter inch	1.38 in
Dimension - L Length Overall mm	130 mm
Dimension - Length Overall inch	5.12 in

### Conductor Related

Conductor - Copper Str Size	500 kcmil
Conductor - Copper Str Size Range	500 kcmil

### Certifications and Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	CM
UL Listed	No

### Logistics

Minimum Pack Quantity	1
-----------------------	---

**For further technical assistance, please contact us**

**BURNDY Headquarters**

47 East Industrial Park Drive  
Manchester, New Hampshire 03109

**Customer Service Hours:**

8 AM - 8 PM Eastern Monday-Friday  
Emergency Service 24-hours/365 Days  
Phone: 1-800-346-4175  
1-603-647-5299 (International)