



BURNDY Catalog Number
UPC Number
Description
Status

YA312TC38
7818108213055
CU HYLUG-350 KCMIL-3/8X1
Active

Web Use
BURNDY Product Line

Dimensional

Tongue Angle
Length (in)
Tongue Type
Barrell Style
Bolt Hole Size (in)
Barrel Type
Thickness
B Length (in)
Pad Width (in)
E - in
Strip Length

Straight
4.49
Standard
Chamfered
0.39
Long
0.18
2.00
1.29
1.00
2-1/16

General

Number of Holes

Product Description

2
Cu Comp Terminal Code Cond, Bvl
Entry, 2 Hole/W/O/InspWindow,
350 kcmil, 350 Navy, 600 V-35
kV, 3/8" Stud, 1.00" Spacing, Lng
bbl, Red, 18 or 324 Index

Conductor(s)

Flex (Class G) Size - Range
Flex (Class H) Size - Range
Flex (Class I) Size - Range
Copper Solid Size (Range)
DLO Size (Range)
Copper Stranded (Range)

N/A
N/A
N/A
N/A
N/A
350 kcmil

Physical

Type of Plating
Bolt Hole Size
Color Code
Plated (Yes or No)
Index Number
Product Material

Tin - Electro Plated
3/8
Red
Y
18,324
Copper

Approvals / Certifications

UL Listed
CSA Certified
ROHS Compatible
UL Recognized
CULUS
Industry Standards
Documentation

Y
Y
Compliant
N
N
UL468A-468B

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
Monday - Friday
Phone: 800-346-4175