



BURNDY Catalog Number	YAV282NFXB
UPC Number	7818100462655
Description	BELLED HYLUG-4/0 FLEX-NE
Status	Active

Web Use
BURNDY Product Line

Dimensional	
Tongue Angle	Straight
Length (in)	5.39
Tongue Type	Standard
Barrell Style	Belled
Bolt Hole Size (in)	0.52
Barrel Type	Long
Thickness	0.14
B Length (in)	1.77
Pad Width (in)	1.14
E - in	1.75
Strip Length	1-7/8
General	
Number of Holes	2
Product Description	Cu Comp Terminal Flex Cond(Telecom), 2 Hole/W/O/InspWindow, 4/0 Str,4/0(550/#24)DLO,4/0 AWG Code, 600 V-35 kV, 1/2" Stud, 1.75" Spacing, Lng bbl, Belled End
Conductor(s)	
Aircraft Cable Size (Range)	N/A
Flex (Class H) Size - Range	4/0 AWG
Flex (Class I) Size - Range	4/0 AWG
Copper Solid Size (Range)	N/A
DLO Size (Range)	4/0 (550/#24) DLO
Navy Cable Size (Range)	N/A
Copper Stranded (Range)	4/0 AWG
Flex (Class G) Size - Range	4/0 AWG
Flex (Class M) Size - Range	4/0 AWG
Physical	
Type of Plating	Tin - Electro Plated
Bolt Hole Size	1/2
Color Code	Purple
Plated (Yes or No)	Y
Index Number	15
Product Material	Copper
Approvals / Certifications	
UL Listed	Y
CSA Certified	Y
ROHS Compatible	Compliant
UL Recognized	N
CULUS	N
Documentation	

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
Monday - Friday
Phone: 800-346-4175