Product data sheet Characteristics

XALD03H7

dark grey empty enclosure lid with light grey base - 3 cut-outs-UL/CSA certified

Product availability: Stock - Normally stocked in distribution facility



Main

Range of product	Harmony XALD	
Product or component type	Empty control station	
Device short name	XALD	
Product destination	For XB5 Ø 22 mm control and signalling units	
Number of cut-out	3 cut-outs	
Colour of base of enclosure	Light grey RAL 7035	
Colour of cover	Dark grey RAL 7016	
Material	Polycarbonate	
Cable entry	2 knock-outs for cable entry, clamping capacity: <= 0.55 in (14 mm) 2 knock-outs for Pg 13 cable gland and ISO M20, clamping capacity: <= 0.47 in (12 mm)	
IP degree of protection	IP69 IP67 IP66 conforming to IEC 60529 IP69K	

Complementary

Assembly style	For customer assembly	- 4
Number of horizontal rows	1	
Number of vertical rows	3	o a
Product weight	0.52 lb(US) (0.238 kg)	
Resistance to high pressure washer	1015.26 psi (7000000 Pa) at 131 °F (55 °C), distance: 0.1 m	5
Mounting of block	Rear mounting Front mounting	2
Electrical composition code	SR1 SF2 SR2 MF2 MF1 PF2 SF1	edain ac. Thie documentals

	PR1 MR1 PF1	
Main group	3 cut-outs	
Group of product	UI -CSA grev	

Environment

Protective treatment	TH	
Ambient air temperature for storage	-40158 °F (-4070 °C)	
Ambient air temperature for operation	-40158 °F (-4070 °C)	
Overvoltage category	Class II conforming to IEC 60536	
NEMA degree of protection	NEMA 13 NEMA 4X	
IK degree of protection	IK03 conforming to EN 50102	
Standards	EN/IEC 60947-1 CSA C22.2 No 14 EN/IEC 60947-5-1 EN/IEC 60947-5-5 UL 508 JIS C 4520 EN/IEC 60947-5-4	
Product certifications	CSA UL	

Ordering and shipping details

Category	22475 - WALL STATIONS
Discount Schedule	CS2
GTIN	00785901114949
Nbr. of units in pkg.	1
Package weight(Lbs)	0.5200000000000002
Returnability	Υ
Country of origin	CZ

Contractual warranty

141 1 1	40 (1	
Warranty period	18 months	