



ADKS

FIXED RESISTANCE, PRE-TERMINATED CABLE

ADKS cables are rated at 5 watts per foot, 120 Vac and have a three wire grounded plug with a 6-foot/2-meter power cord. Roof and gutter de-icing kits include the appropriate number of roof clips and cable spacers. ADKS cables are UL Listed to Canadian Safety Standards and CSA Certified.



CATALOG NUMBER	DESCRIPTION	CTN QTY	CTN WGT	UPC	CERTIFICATIONS
ADKS100 *	20' length, 100 watts	5	8	0-13627-10969-8	 
ADKS150 *	30' length, 150 watts	5	9	0-13627-10970-4	
ADKS300 *	60' length, 300 watts	5	13	0-13627-10971-1	
ADKS400 *	80' length, 400 watts	5	16	0-13627-10972-8	
ADKS500 *	100' length, 500 watts	5	17	0-13627-10973-5	
ADKS600	120' length, 600 watts	2	10	0-13627-10974-2	
ADKS800	160' length, 800 watts	2	12	0-13627-10975-9	
ADKS1000	200' length 1000 watts	2	15	0-13627-10976-6	
ADKS1200	240' length, 1200 watts	2	17	0-13627-10977-3	
RKCADKS	Starter Assortment: one each of *d kits above	1 set	14	0-13627-07042-4	
RKFADKS	Assortment: two each of *d kits above; (1) RS2	1 set	27	0-13627-07001-1	
CSK12	Clips (19) and Spacers (16)	10 bags	2	0-13627-10814-1	

ADKS CONTROL

RESIDENTIAL ROOF AND GUTTER DE-ICING CONTROL

Roof Sentry® RS2 – This residential grade unit automatically controls operation and energy usage of electric roof de-icing cable. The RS2 requires two conditions to be present before it energizes roof de-icing cable: both cold temperatures (on, 38°F/3°C; off, 48°F/9°C) and the presence of run-off water from the roof in contact with its sensor wire. If only one of the conditions exists, the control will not energize the cable. The control is rated at 10 amps at 120 Vac, and requires one per cable. The RS2 control is CSA Certified.



CATALOG NUMBER	DESCRIPTION	CTN QTY	CTN WGT	UPC	CERTIFICATIONS
RS2	Roof Sentry control for ADKS cables	5	10	0-13627-09862-6	