


In the world of power transmission and distribution, look to Hubbell

Catalog Home

Product Datasheet

CHANCE

M50T26 -- Type T (ANSI) Cutout Fuselink



50 amp, Type T (ANSI) Cutout fuselink with a 26" (660.4mm) pigtail.

Product Specifications	
Туре	Fuselinks
Fuselinks	Type T (ANSI)
Amp Rating	50
Removable Buttonhead	No
Pigtail Length	26" (660.4mm)
PDF Catalog Page	
	Click <u>HERE</u> to view detailed PDF Catalog
Fuse Link Application Guide and Time-Current Curves	Click HERE and request, Fuse Links (Bulletin 10-7701).
Fuse Element	Stainless-steel strain wire and a pure-tin fuse wire
Required Cutout Fuseholder	100 Amp (Do not use in a 200 amp fuseholder.)
Material Type	Non-Standard
UPC Code	09635904882
Standard Package	10
Standard Package Unit	Each
Min Order Qty	10
Pallet Quantity	4800

Notes

Can not be used with an arc-shortening rod in fuseholder.

Compressed Product Number

M50T26

Catalog Home



Warranty Info | Trademarks | Terms of Use

All contents Copyright © 2007 Hubbell Power Systems, Inc. All rights reserved.

NOTE: Because Hubbell has a policy of continuous product improvement, we reserve the right to change design and specifications without notice.