



[Catalog Home](#)

Product Datasheet

CHANCE

C6002626 -- Terminal, Plug Assembly



Shrouded ferrules overlap onto the grounding cable jacket for stress relief to the terminal. Two crimps secure the ferrule against the bare strands and one crimp applies on the jacket. Available either factory-installed in pairs on any cable length specified or as separate individual units, the ferrules install simply with a hydraulic crimping tool. Complete illustrated installation instructions come with the ferrules and include a table for the crimping die sizes to use.

Product Specifications

Product Type	Ferrules
Cable Size	#2
Material	Aluminum
Terminal Type	Pressure or Plain
Shroud	Shrouded
Continuous Current	200 Amps
Fault Current - 15 cycles	14,000 Amps
Fault Current - 30 cycles	10,000 Amps
Section A Burndy Die Number	U165
Section B Burndy Die Number	U166
Material Type	Non-Standard
UPC Code	09635923319
Standard Package	1
Standard Package Unit	Each
Min Order Qty	1
Weight / Ea.	0.157 lbs

Compressed Product Number

C6002626

[Catalog Home](#)



[Warranty Info](#) | [Trademarks](#) | [Terms of Use](#)

All contents Copyright © 2007 Hubbell Power Systems, Inc. All rights reserved.

NOTE: Because Hubbell has a policy of continuous product improvement, we reserve the right to change design and specifications without notice.