



COUPLING BOLT FOR
EXTENSIONS AND ADAPTERS
P0010041P

COUPLING NUT
055449P



THIMBLEYE
ADAPTER
C1020023




TWINEYE
ADAPTER
C1020024



TWINEYE ADAPTER
WITHOUT PULLING EYE
C1020024A




TRIPLEYE
ADAPTER
C1020025



TRIPLEYE ADAPTER
WITHOUT PULLING EYE
C1020025A



DVALEYE
ADAPTER
C1100041



TRIPLEYE SHACKLE
C1100574



PLAIN
EXTENSION

CAT. NO.	"L"
12655	37-3/4"
12656	57-1/2"
12657	80-1/2"
12658	120"

NOTES

- HOT DIP GALVANIZED PER ASTM A153 (LATEST REVISION)
- LENGTH DIMENSIONS ARE NOMINAL
- SHAFT MATERIAL: HOT ROLLED-CORNERED SQUARE (RCS) SOLID STEEL BARS PER ASTM A29, MINIMUM YIELD STRENGTH = 70 KSI
- HELIX MATERIAL: HOT ROLLED LOW CARBON STEEL SHEET, STRIP, OR PLATE PER ASTM A572; OR A1018 GRADE 50, MINIMUM YIELD STRENGTH = 50 KSI. 3/8" THICK
- COUPLING BOLTS: 3/4" DIAMETER X 3" LONG HEX HEAD PER ASTM A325 TYPE I.
- NOMINAL SPACING BETWEEN HELICAL PLATES IS THREE TIMES THE DIAMETER OF THE LOWER HELIX
- MANUFACTURER HAS IN EFFECT INDUSTRY RECOGNIZED WRITTEN QUALITY CONTROL FOR ALL MATERIALS AND MANUFACTURING PROCESSES
- ALL WELDING PERFORMED BY WELDERS CERTIFIED UNDER SECTION 5 OF THE AWS CODE D1.1
- COUPLINGS ARE HOT UPSET FORGED SOCKETS FORMED AS AN INTEGRAL PART OF THE PLAIN EXTENSION MATERIAL
- ADD USA SUFFIX TO CATALOG NUMBER FOR BUY AMERICA ITEMS. PURCHASERS OF BUY AMERICA ITEMS WILL BE PROVIDED A DATED CERTIFICATE OF COMPLIANCE TO SPECIFIC BUY AMERICA PROVISIONS IF REQUESTED AT THE TIME OF ORDER. CONTACT HUBBELL POWER SYSTEMS CUSTOMER SERVICE FOR DETAILS.

- TORQUE RATING: 5,700 FT-LB
- ULTIMATE CAPACITY* (TENSION/COMPRESSION): 57 KIP
- *BASED ON A TORQUE FACTOR (Kt)=10
- ULTIMATE TENSION STRENGTH (COUPLING BOLT): 70 KIP

CHANCE®		HUBBELL® POWER SYSTEMS	
CONFIDENTIAL: THIS DRAWING AND ITS CONTENTS ARE CONFIDENTIAL AND THE EXCLUSIVE PROPERTY OF HUBBELL POWER SYSTEMS. NO PUBLICATION, DISTRIBUTION OR COPIES MAY BE MADE WITHOUT THE WRITTEN CONSENT OF HUBBELL POWER SYSTEMS. HUBBELL POWER SYSTEMS UNPUBLISHED ALL RIGHTS RESERVED UNDER THE COPYRIGHT LAWS.		TITLE SS5 ANCHORS	
SIZE SB	DWG NO. SA110-10000	CAT / PART / ASSY NO. SEE CHART	REV Q
DO NOT SCALE THIS DRAWING	DRN BY NJM	DATE 07/06/17	SHEET 1 OF 1