



SAFETY DATA SHEET

1. Identification

Product identifier Copper Anti-Seize & Lubricating Compound

Other means of identification

Product code SL35901, SL35903

Recommended use Anti-seize and lubricating compound

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufactured or sold by:

Company name CRC Industries, Inc.
Address 885 Louis Dr.
Warminster, PA 18974 US
Telephone
General Information 215-674-4300
Technical Assistance 800-521-3168
Customer Service 800-272-4620
24-Hour Emergency (CHEMTREC) 800-424-9300 (US)
703-527-3887 (International)
Website www.crcindustries.com

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Not classified.

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements

Hazard symbol None.

Signal word None.

Hazard statement The mixture does not meet the criteria for classification.

Precautionary statement

Prevention Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. Observe good industrial hygiene practices.

Response Wash hands after handling.

Storage Store away from incompatible materials.

Disposal Dispose of contents/container in accordance with local/regional/national regulations.

Hazard(s) not otherwise classified (HNOC) None known.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Distillates (petroleum), hydrotreated heavy naphthenic		64742-52-5	50 - 60
Residual oils (petroleum), hydrotreated		64742-57-0	10 - 20
Talc (not containing asbestos fibers)		14807-96-6	10 - 20
Calcium carbonate		1317-65-3	5 - 10
Copper		7440-50-8	5 - 10

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Call a physician if symptoms develop or persist.
Skin contact	Remove and isolate contaminated clothing and shoes. Wash off immediately with soap and plenty of water. Get medical attention if irritation develops and persists. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Drink plenty of water. Never give anything by mouth to a victim who is unconscious or is having convulsions. Do not induce vomiting without advice from poison control center. Get medical advice/attention if you feel unwell.
Most important symptoms/effects, acute and delayed	Direct contact with eyes may cause temporary irritation.
Indication of immediate medical attention and special treatment needed	Treat symptomatically.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media	Water spray. Carbon dioxide (CO ₂). Foam. Dry powder.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire-fighting equipment/instructions	Cool containers exposed to heat with water spray and remove container, if no risk is involved.
General fire hazards	No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	This product is miscible in water. Prevent further leakage or spillage if safe to do so. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Prevent entry into waterways, sewer, basements or confined areas. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases.

7. Handling and storage

Precautions for safe handling	Provide adequate ventilation. Wear appropriate personal protective equipment. When using, do not eat, drink or smoke. Observe good industrial hygiene practices. Avoid release to the environment. Use care in handling/storage. For product usage instructions, please see the product label.
Conditions for safe storage, including any incompatibilities	Keep container tightly closed in a dry and well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Calcium carbonate (CAS 1317-65-3)	PEL	5 mg/m ³	Respirable fraction.
		15 mg/m ³	Total dust.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Copper (CAS 7440-50-8)	PEL	1 mg/m ³ 0.1 mg/m ³	Dust and mist. Fume.
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	PEL	5 mg/m ³	Mist.
Residual oils (petroleum), hydrotreated (CAS 64742-57-0)	PEL	2000 mg/m ³ 500 ppm 5 mg/m ³	Mist.

US. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Type	Value	Form
Talc (not containing asbestos fibers) (CAS 14807-96-6)	TWA	0.3 mg/m ³	Total dust.
		0.1 mg/m ³ 20 mppcf	Respirable.
		2.4 mppcf	Respirable.

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	TWA	5 mg/m ³	Inhalable fraction.
Residual oils (petroleum), hydrotreated (CAS 64742-57-0)	TWA	5 mg/m ³	Inhalable fraction.
Talc (not containing asbestos fibers) (CAS 14807-96-6)	TWA	2 mg/m ³	Respirable fraction.

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Calcium carbonate (CAS 1317-65-3)	TWA	5 mg/m ³	Respirable.
Copper (CAS 7440-50-8)	TWA	10 mg/m ³ 1 mg/m ³	Total Dust and mist.
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	Ceiling	1800 mg/m ³	
	STEL	10 mg/m ³	Mist.
	TWA	5 mg/m ³	Mist.
Residual oils (petroleum), hydrotreated (CAS 64742-57-0)	STEL	10 mg/m ³	Mist.
	TWA	5 mg/m ³	Mist.
Talc (not containing asbestos fibers) (CAS 14807-96-6)	TWA	2 mg/m ³	Respirable.

Biological limit values

No biological exposure limits noted for the ingredient(s).

Exposure guidelines

Occupational Exposure Limits are not relevant to the current physical form of the product.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection	Wear safety glasses with side shields (or goggles).
Skin protection	
Hand protection	Wear protective gloves such as: Nitrile. Polyvinyl chloride (PVC).
Other	Wear suitable protective clothing.
Respiratory protection	If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state	Solid.
Form	Semi-solid gel.
Color	Copper.
Odor	Petroleum.
Odor threshold	Not available.
pH	Neutral
Melting point/freezing point	> 449.6 °F (> 232 °C)
Initial boiling point and boiling range	> 500 °F (> 260 °C)
Flash point	> 429.8 °F (> 221 °C) Cleveland Open Cup
Evaporation rate	Very slow.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	0.9
Flammability limit - upper (%)	7
Vapor pressure	< 0.01 kPa
Vapor density	> 5 (air = 1)
Relative density	1.09
Solubility (water)	Insoluble.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	> 500 °F (> 260 °C)
Decomposition temperature	Not available.
Viscosity (kinematic)	Not available.
Percent volatile	0 %

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Heat, flames and sparks. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents. Acetylene. Vinyl compounds.
Hazardous decomposition products	Carbon oxides. Hydrocarbon fumes and smoke.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.
Skin contact	Prolonged skin contact may cause temporary irritation.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	May be harmful if swallowed. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Symptoms related to the physical, chemical and toxicological characteristics Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity

Product	Species	Test Results
Copper Anti-Seize & Lubricating Compound		
Acute		
Dermal		
LD50	Rabbit	3760 mg/kg estimated
Oral		
LD50	Rat	2372 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.
Respiratory sensitization	Not a respiratory sensitizer.
Skin sensitization	This product is not expected to cause skin sensitization.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	Not classified.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	Not an aspiration hazard.
Further information	This product has no known adverse effect on human health.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Product	Species	Test Results
Copper Anti-Seize & Lubricating Compound		
Aquatic		
<i>Acute</i>		
Crustacea	LC50	Calanoid copepod (<i>Acartia tonsa</i>) > 1000 mg/l, 48 hours
Fish	LC50	Flatfish, flounder (<i>Scophthalmus maximus</i>) > 1000 mg/l, 96 hours
Other	EC50	Diatom (<i>Skeletonema costatum</i>) > 1000 mg/l, 72 hours

Components	Species		Test Results
Copper (CAS 7440-50-8)			
Aquatic			
<i>Acute</i>			
Crustacea	EC50	Water flea (Daphnia magna)	0.03 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	0.052 mg/l, 96 hours
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	1000 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	5000 mg/l, 96 hours
Talc (not containing asbestos fibers) (CAS 14807-96-6)			
Aquatic			
<i>Acute</i>			
Fish	LC50	Zebra danio (Danio rerio)	> 100 g/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability	No data is available on the degradability of this product.
Bioaccumulative potential	No data available.
Mobility in soil	No data available.
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal of waste from residues / unused products	This product is not a RCRA hazardous waste (See 40 CFR Part 261.20 – 261.33). Empty containers may be recycled. Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose in accordance with all applicable regulations.
Hazardous waste code	Not regulated.
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information

DOT	Not regulated as dangerous goods.
IATA	Not regulated as dangerous goods.
IMDG	Not regulated as dangerous goods.

15. Regulatory information

US federal regulations	This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.	
TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)	Not regulated.	
US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)	Not listed.	
SARA 304 Emergency release notification	Not regulated.	
US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance	Copper (CAS 7440-50-8)	
CERCLA Hazardous Substance List (40 CFR 302.4)	Copper (CAS 7440-50-8)	Listed.
CERCLA Hazardous Substances: Reportable quantity	Copper (CAS 7440-50-8)	5000 LBS

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

Food and Drug Administration (FDA) Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 311/312 Hazard categories Immediate Hazard - No
Delayed Hazard - No
Fire Hazard - No
Pressure Hazard - No
Reactivity Hazard - No

SARA 302 Extremely hazardous substance No

US state regulations

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Copper (CAS 7440-50-8)
Talc (not containing asbestos fibers) (CAS 14807-96-6)
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)
Residual oils (petroleum), hydrotreated (CAS 64742-57-0)

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. New Jersey Worker and Community Right-to-Know Act

Calcium carbonate (CAS 1317-65-3)
Talc (not containing asbestos fibers) (CAS 14807-96-6)
Copper (CAS 7440-50-8)
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)
Residual oils (petroleum), hydrotreated (CAS 64742-57-0)

US. Massachusetts RTK - Substance List

Calcium carbonate (CAS 1317-65-3)
Copper (CAS 7440-50-8)
Residual oils (petroleum), hydrotreated (CAS 64742-57-0)
Talc (not containing asbestos fibers) (CAS 14807-96-6)

US. Pennsylvania Worker and Community Right-to-Know Law

Copper (CAS 7440-50-8)
Calcium carbonate (CAS 1317-65-3)
Residual oils (petroleum), hydrotreated (CAS 64742-57-0)
Talc (not containing asbestos fibers) (CAS 14807-96-6)

US. Rhode Island RTK

Copper (CAS 7440-50-8)

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

Volatile organic compounds (VOC) regulations

EPA

VOC content (40 CFR 51.100(s)) 0 %

Consumer products (40 CFR 59, Subpt. C) Not regulated

State

Consumer products This product is regulated as an Anti-seize Lubricant (non-aerosol). This product is compliant for use in all 50 states.

VOC content (CA) 0 %

VOC content (OTC) 0 %

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	05-21-2015
Prepared by	Allison Cho
Version #	01
Further information	Not available.
HMIS® ratings	Health: 1 Flammability: 1 Physical hazard: 0 Personal protection: B
NFPA ratings	Health: 1 Flammability: 1 Instability: 0

NFPA ratings



Disclaimer

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries.