261 Cahaba Valley Parkway Pelham, AL 35124-1146

Tel: 1.800.637.6047 / 205.733.0333 Fax: 1.800.521.6896 / 205.733.8930

www.rainbowtech.net Woman-Owned Business Enterprise Founded 1971

Safety Data Sheet (SDS)

1 Identification of substance

Trade name:

ELECTRIC RED MARKING PAINT

Product number:

Issue Date:

Replaces MSDS Dated: April 8, 2014

January 14, 2021

Manufacturer/Supplier:

Rainbow Technology Corporation 261 Cahaba Valley Parkway Pelham, Alabama 35124

(800) 637.6047, www.rainbowtech.net

Contact person: Larry Joe Steeley, Jr.

CHEMTEL 1-800-255-3924, 813-248-0585 if located outside the U.S. **Emergency information:**

2 Composition/Data on components

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components: 64742-89-8 VM&P Naptha 18.33% 1317-65-3 Calcium Carbonate 15.38% 106-97-8 n-butane 10.36% 64742-47-8 Mineral Spirits 5.18%

Additional information: For the wording of the listed risk phrases refer to section 3.

3 Hazards identification

Hazard description:



Irritant Flammable

Physical dangers:

Flammable liquid and vapor in a pressurized container. Keep away from heat, sparks, and flame.

Flammable.

Irritating to eyes.

Keep out of the reach of children.

Effects of short-term

overexposure:

Vapors cause irritation to the eyes, nose, throat, skin, and central nervous system. Symptoms may

include dizziness, throat irritation, headache, fatigue, swelling of eyes, and nausea.

Effects of chronic

overexposure:

May cause permanent brain and nervous system damage. Repeated overexposure can also damage kidneys, lungs, liver, heart, and blood. Intentional misuse by deliberately inhaling the contents may be

harmful or fatal.

NFPA ratings (scale 0 - 4): Health-

Flammability-

Reactivity-

HMIS-ratings (scale 0 - 4): Health-

Flammability- 3 Physical Hazard-3

4 First aid measures

After inhalation:

Supply fresh air; consult doctor in case of complaints.

After skin contact:

Remove contaminated clothing. Wash exposed area with soap and water.

After eye contact:

Move to fresh air. Rinse opened eye for several minutes under running water. If symptoms persist,

consult a doctor.

After swallowing:

Contact physician or poison control center.

5 Fire fighting measures

Extinguishing agents:

CO2, sand, extinguishing powder, or water spray. Fight larger fires with water spray or alcohol resistant

foam.

Protective equipment:

No special measures required.

6 Accidental release measures

Personal safety

precautions:

Wear protective equipment. Keep unprotected persons away.

Environmental safety precautions:

Inform appropriate authorities in case of seepage into water course or sewage system.

Do not allow product to reach sewage systems or ground water.

(Contd. on page 2)

Safety Data Sheet (SDS)

Trade name: ELECTRIC RED MARKING PAINT

(Contd. of page 1)

Measures for cleaning/

collecting:

Do not flush with water or aqueous cleansing agents. Use diluted caustic solution. Soak up spills with

inert absorbent material. Refer to section 13 for disposal information.

7 Handling and storage

Fire/explosion protection: Do not spray on a naked flame or any incandescent material.

Do not smoke. Protect from electrostatic charges.

Storage requirements: Observe pressurized container storage regulations. Consult with your local authorities.

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions.

8 Exposure controls and personal protection:

Components with limit values that require monitoring at the workplace:

106-97-8 n-butane

REL 1900 mg/m³, 800 ppm

Protective hygienic

measures: Keep away from foodstuffs and animal feed. Wash hands after use.

Breathing equipment:

Use suitable respiratory protective device in case of insufficient ventilation.

A respirator is generally not necessary when using this product outdoors or in large open areas. In cases

of inadequate ventilation, a respiratory protective device should be worn to prevent overexposure. Protective gloves. The glove material has to be impermeable and resistant to the substance. No glove **Protection of hands:**

recommendation can be given.

Tightly sealed goggles Eye protection:

9 Physical and chemical properties:

General Information: Color: Odor: Boiling point/Boiling range:	According to trade name description in section 1. Solvent -44°C (-47°F)
Flash point:	-19°C (-2°F)
Ignition temperature:	210.0°C (410°F)
Auto igniting:	Product is not self-igniting.
Danger of explosion: Lower Explosion Limit: Upper Explosion Limit: Vapor Pressure:	Stable at normal temperatures. Can may burst when exposed to temperatures exceeding 120 degrees fahrenheit. In use, may form flammable/explosive vapour-air mixture. 0.9 Vol % 10.9 Vol % 40 PSI, 2750 hPa
Density: Specific Gravity:	Not determined. Between 0.77 and 0.85 (Water equals 1.00)
VOC content: VOC in weight percent (less aceton Water:	663.0 g/l / 5.53 lb/gl ne): 52.4 % 21.0 %
Solids content:	25.6 %

10 Stability and reactivity:

Conditions to be avoided: Do not allow the can to exceed 120 degrees Fahrenheit. Stable at normal temperatures.

Possibility of Hazardous

Reactions: No dangerous reactions known.

11 Toxicological information:

Primary effect on the skin: No irritant effect. Primary effect on the eye: Irritating effect.

No sensitizing effects known. **Sensitization:**

12 Ecological information

Other information: This product does not contain any chloroflourocarbons (CFC's), chlorinated solvents, lead, mercury,

cadmium, hexavalent chromium, polybrominated biphenyl (PBB), or polybrominated diphenyl ether (PDBE). No specific ecological data is available for this product.

(Contd. on page 3)

Safety Data Sheet (SDS)

Trade name: ELECTRIC RED MARKING PAINT

Harmful to aquatic organisms.

Hazardous for water, do not empty into drains.

13 Disposal considerations

Acquatic toxicity:

DISPOSAL METHOD: Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation: Empty cans should be recycled.

14 Transport information:

Hazard class: 2.1 N/A **Identification number:** Label

2.1 2 5F Gases ADR/RID class: **UN-Number:** 1950 **IMDG Class:** 2.1 Packaging group: П **EMS Number:** F-D,S-U Marine pollutant: No ICAO/IĀTA Class:

Aerosols, Flammable **Propper shipping name:**

15 Regulations

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

TSCA (Toxic Substances

All ingredients are listed. Control Act):

PROPOSITION 65 Chemicals known to cause cancer:

None of the ingredients in this product are listed.

Canadian WHMIS: Class A, B5---Flammable Aerosols

EPA:

A= Known human carcinogen B= Probable human carcinogen

C= Possible human carcinogen

D= Not classifiable as to human carcinogenicity: Inadequate human and animal evidence of carcinogenicity (or no data is available).

IARC:

Group 2B: The ingredient is possibly carcinogenic to humans. There is limited evidence of carcinogenicity.

Group 3: The ingredient is unclassifiable as to its carcinogenicity to humans.

A1-designates a confirmed human carcinogen.

A2-designates a suspected human carcinogen.

A3-designates an animal carcinogen. A4-designates "not classifiable as a human carcinogen".

NIOSH:

None of the ingredients is listed.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Regulatory Affairs Contact:

(Contd. of page 2)