



[Catalog Home](#)

Product Datasheet

ANDERSON FARGO

GD115 -- Copper Automatic Dead End



Copper Automatic Dead End, Copper, CW Conductor .28 - .29" (7.2 - 7.4 mm) , Flex Bail

Product Specifications

Category Image



Automatic Deadends
Copper and Aluminum
AAC, AAAC, ACAR, ACSR,
Copper & Copperweld®
Conductor

Series Image (Automatic)



GD-100 Series
Automatic Dead End
Flex Bail
Copper & Copperweld®
Conductor

PDF Catalog Page

[Click HERE to view the web page.](#)

Bail Option

Flex Bail

Type

Automatic

Material

Copper

Inhibitor Loaded

Yes

Shell Material

Copper Alloy

Bail Material

Stainless Steel

Diameter Range

.28 - .29 in (7.2 - 7.4 mm)

Conductor Range Minimum - Maximum

Cu 1 sol, Cu 2 str (7), CW 4A

Minimum Conductor Diameter

0.28

Maximum Conductor Diameter

0.29

Weight / Ea.

0.45 lbs

Standard Package

50

UPC Code

09635930807

Notes

Add "N" suffix for Neoprene coated bail.

Compressed Product Number

GD115

[Catalog Home](#)



[Warranty Info](#) | [Trademarks](#) | [Terms of Use](#)

All contents Copyright © 2007 Hubbell Power Systems, Inc. All rights reserved.

NOTE: Because Hubbell has a policy of continuous product improvement, we reserve the right to change design and specifications without notice.