



Catalog Number: Product ID: UPC Number: Status:

M-53 7TAH007070R0072 78621076353 Active

ALUMA-SHIELD Aluminum Joint Compound, 5 Gallon Can, for Aluminum Cable Connections

- Contains fine zinc particles which break through the oxide film on cable strands upon compression of connection.
- #N/A
- Electrical and Mechanical Connections

Representative	
----------------	--

North American Specifications	(UNSPSC)
UNSPSC	39121337 Electrical sealing compound
IGCC	4496 Electrical sealing compound
Brand Name	Color-Keyed
Туре	Sealants & amp; Lubricants
Special Features	Contains fine zinc particles which break through the
	oxide film on cable strands upon compression of
	connection.
Application	Electrical and Mechanical Connections
Size	5 Gallon
Container	Can
Temperature Range	-50 Degrees F to 250 Degrees F
Material	Compound
Color	Gray

European Specifications (ETIM)

ETIM	EC002722 Jointing compound
Model	Other
Colour	Grey
Packaging	Can
Volume	18927.1ml

Packaging

Outer Quantity	1
Outer Dimensions (inches)	18x18x24
Weight Uom	64 lbs. Each

Documents / Support Tools

Technical Drawing / Data Sheet USAvailable on WebsiteTechnical Drawing / Data Sheet CanadaAvailable on WebsiteSafety Data Sheet (SDS) GlobalSDS-00012-TB2

For further technical assistance, please contact us...

ABB Installation Products Technical Support MS 3B-50 860 Ridge Lake Blvd. Memphis, TN 38120 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com

ABB Installation Products - USA 860 Ridge Lake Blvd. Memphis, TN 38120 www.tnb.com