



MEGASTRETCH™ HI-STRETCH NON-DETECTABLE TAPE 3" x 6000'

Stretches up to 10 times its length before breaking; its blended polymers create a unique, strong-yet-stretchable warning tape for the telecommunications industry. Unique polymer gives stretch and strength needed for plowed installations. This combination also provides the stretch properties needed for increased visibility during accidental digins. "Plow-mount-ready" super-length spools minimize roll changes. Wound onto heavyduty, wax-impregnated cores designed withstand the rigors of the job site.

INCLUDES:

(1) MEGASTRETCH™ HI-STRETCH NON-DETECTABLE TAPE (25-071)

FEATURES:

- Environmentally safe
- Lead free
- Permanent messaging
- Wear resistant

PRODUCT SPECIFICATIONS:

Feature	Method	Value (English)	Value (SI)
Overall Thickness	ASTM D-2103	4.0 mil (Nominal)	0.1 mm (Nominal)
Weight	ASTM D-2103	17.88 lbs / 1,000 ft ²	8.73 kg / 100 m ²
Tensile Strength	ASTM D-882	Length: 6,340 psi	Length: 43.71 Mpa
Elongation	ASTM D-882	Length: 867%	Length: 867%
Printability	ASTM D-2578		> 40 dynes
Plastic Density	ASTM D-792-08		.928 g/cc