# Thomas&Betts



Representative

### Catalog Number: Product ID: UPC Number: Status:

DG4X1C-500 7TAA241030R0063 79120720108 Active

Riser-Gard Fiber Optic Corrugated Conduit, Size 1-1/4 Inch, Outer Diameter 1.67 Inch, Inner Diameter 1.31 Inch, Wall Thickness 0.080 Inch, Length 500 Feet, Material PVC, Color Orange, with Pull Tape

## North American Specifications (UNSPSC)

North American opecin	
UNSPSC	39131706 Electrical conduit
IGCC	5535 Electrical conduit
Brand Name	Carlon
Туре	Riser-Gard Flexible Raceway
Special Features	UL Listed and is available with tape pre-installed.
Application	Riser-Gard is suitable for use in vertical runs in a
	shaft or between floors, as well as areas other than
	the plenum.
Standard	UL e151168
Trade Size	1-1/4 Inch
Outside Diameter	1.67 Inches
Inside Diameter	1.31 Inches
Length	500 ft
Material	PVC
Color	Orange

#### **European Specifications (ETIM)**

Luiopean opecifications (Linn	/
ETIM	EC001175 Corrugated plastic hose
Nominal diameter	31.75mm
Nominal size in inch	1 1/4 inch
Outer diameter	42.4mm
Inner diameter	33.3mm
Material	PVC
Operating temperature	-20 - +40°C
UV resistant	Ν
Colour	Orange
Sheathing material	Not sheathed
Approved according to DIN EN 61386-23	Ν
Approved according to UR	Ν
Approved according to LUL/British Stan-	Ν
dard	
Approved according to Lloyd's Register	Ν
ТА	
Approved according to UTAC	Ν
Approved according to DIN 5510	Ν
Approved according to NF F 16-101	N
Packaging	
Outer Quantity	500
Outer Dimensions (inches)	1x1x1

0.17 lbs. Each

#### **Documents / Support Tools**

Weight Uom

Technical Drawing / Data Sheet	WSD-AC04182
Technical Drawing / Data Sheet Canada	Available on Website

For further technical assistance, please contact us...



ABB Installation Products - USA 860 Ridge Lake Blvd. Memphis, TN 38120 www.tnb.com ABB Installation Products Technical Support MS 3B-50 860 Ridge Lake Blvd. Memphis, TN 38120 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com