

Actual

Catalog Number: CSS-LH

 Product ID:
 7TAA159150R0000

 UPC Number:
 78621070172

 EAN Number:
 05414363149910

Status: Active

Deltec Cable Tie Locking Head Only, Black Acetal for Temperatures up to 105 Degrees Celsius (221 F), Length of 21.59mm (0.85 Inches), Width of 19.05mm (0.75 Inch), Height of 12.57mm (0.495 Inch), Weather and Ultraviolet Resistant, Bulk Pack

- Perfect for coaxial, fiber optic and all other communication and electrical conducting cables.
- Strap and body are weatherable acetal, offering superior resistance to sunlight, moisture and salt environments.
- Locking device is marine-grade corrosion-resistant copper alloy.
- Application Tools: WT3D

North American Specifications (UNSPSC)		
UNSPSC	39121703 Cable ties	
IGCC	5034 Cable ties	
Brand Name	Deltec	
Туре	Head (Buckle)	
Special Features	Perfect for coaxial, fiber optic and all other commu-	
	nication and electrical conducting cables.	
Application	Ideal solution for bundling in harsh outdoor environ-	
	ments.	
Width	0.75 in ; 19.05 mm	
Length	0.85 in ; 21.59 mm	
Material	Weather Resistant Acetel	
Color	Black	
Lock Mechanism	Double Locking Head	
Tensile Strength	250 Pounds/1112 Newtons	

European Specifications (ETIM)		
ETIM	EC000046 Cable tie	
Band width	19.05mm	
Length belt/tape/tie	21.59mm	
Operating temperature	-40-+105°C	
Model	Internal toothing	
Band closure	Double lock head	
Material	Plastic	
Material quality	Polyoxymethylene (POM)	
Surface protection	Untreated	
Halogen free	Υ	
Colour	Black	
Transparent	N	
Reflective (fluorescent)	N	
Text strip	None	
Solvable fastener	N	
MIL approval	N	

Packaging	
Inner Quantity	25
Outer Quantity	500
Outer Dimensions (inches)	9.5x6.5x5.5
Weight Uom	0.5 lbs. per 100



Documents / Support Tools

Technical Drawing / Data Sheet US Available on Website

For further technical assistance, please contact us...

ABB Installation Products - USA 860 Ridge Lake Blvd. Memphis, TN 38120 www.tnb.com

ABB Installation Products Technical Support MS 3B-50 860 Ridge Lake Blvd. Memphis, TN 38120

Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com