



Straight Blade Devices




HBL5865VY




HBL5869VY




HBL5302



HBL5929



HBL9758VY



HBL5552B

Dimensions in Inches (mm)



15A, 125V, 2 Pole, 2 Wire Non-Grounding, Valise® Plugs

IP20
SUITABILITY



15A 125V
NEMA 1-15R
UL CSA
0.5 HP



15A 125V
NEMA 1-15P
UL CSA
0.5 HP

Description	Cord Diameter	Catalog Number	
Yellow nylon, non-polarized.	.218"-.385" (5.5-9.8)	-	HBL5865VY
Yellow nylon, polarized.	.218"-.385" (5.5-9.8)	-	HBL5866VY
Black nylon, polarized.	Type 17/2 "SVT" cord	-	HBL5867VBLK

Valise® Connector Bodies

Description	Cord Diameter	Catalog Number	
Yellow nylon.	.218"-.385" (5.5-9.8)	HBL5869VY	-



15A, 277V AC, 2 Pole, 3 Wire Grounding, Plugs



15A 277V AC
NEMA 7-15R
UL CSA
2 HP



15A 277V AC
NEMA 7-15P
2 HP

Description	Cord Diameter	Catalog Number	
Finger grip, black elastomer.	.31"-.43" (7.9-10.9)	-	HBL5929*

Receptacles and Connector Bodies

Description	Cord Diameter	Catalog Number	
Receptacle, flush duplex, brown, back and side wired.	-	HBL5302	-
Connector Body, phenolic and steel body.	.296"-.625" (7.5-15.9)	HBL5324	-

Note: *Not UL Listed.
Horsepower ratings are AC only.
See pages A-47 and A-48 for accessories.



20A, 250V, 2 Pole, 2 Wire Non-Grounding, Valise® Plugs

IP20
SUITABILITY



20A 250V
NEMA 2-20R
UL Listed
2 HP



20A 250V
NEMA 2-20P
UL Listed
2 HP

Description	Cord Diameter	Catalog Number	
Yellow nylon.	.220"-.660" (5.6-16.8)	-	HBL9758VY

Receptacle, Single

Description	Catalog Number	
Black phenolic.	HBL5552B	-

Note: Horsepower ratings are AC only and apply to plugs and receptacles only.
See pages A-47 and A-48 for accessories.