

**HBL9460A**

## 60A, 125/250V, 3 Pole, 4 Wire Grounding, Receptacles and Plugs

**IP20**  
SUITABILITY



**60A 125/250V  
NEMA 14-60R  
UL CSA  
3(2) HP**



**60A 125/250V  
NEMA 14-60P  
UL CSA  
3(2) HP**

Description	Cord Diameter	Catalog Number
Receptacle, black RTP.	-	<b>HBL9460A</b>
Plug, nylon.	.625"-1.310" (15.9-33.3)	- <b>HBL9461C</b>
Plug, nylon, angle, 4-position.	.625"-1.310" (15.9-33.3)	- <b>HBL9462C</b>



**HBL9461C**

## 60A, 3Ø 250V AC, 3 Pole, 4 Wire Grounding, Receptacles and Plugs

**IP20**  
SUITABILITY




**60A 3Ø 250V AC  
NEMA 15-60R  
UL CSA  
10 HP**



**60A 3Ø 250V AC  
NEMA 15-60P  
UL CSA  
10 HP**

Description	Cord Diameter	Catalog Number
Receptacle, black RTP.	-	<b>HBL8460A</b>
Plug, nylon.	.625"-1.310" (15.9-33.3)	- <b>HBL8461C</b>
Plug, nylon, angle, 4-position.	.625"-1.310" (15.9-33.3)	- <b>HBL8462C</b>



**HBL9462C**

## 60A, 3ØY 120/208V AC, 4 Pole, 4 Wire Non-Grounding, Receptacles and Plugs

**IP20**  
SUITABILITY




**60A 3ØY  
120/208V AC  
NEMA 18-60R  
UL Listed  
7.5 HP**



**60A 3ØY  
120/208V AC  
NEMA 18-60P  
UL Listed  
7.5 HP**

Description	Cord Diameter	Catalog Number
Receptacle, black RTP.	-	<b>HBL7301A</b>
Plug, nylon.	.625"-1.310" (15.9-33.3)	- <b>HBL7303C</b>
Plug, nylon, angle, 4-position.	.625"-1.310" (15.9-33.3)	- <b>HBL7302C</b>



**HBL7301A**

*Note: RTP is an abbreviation for reinforced thermoplastic polyester.  
See page A-50 for accessories.*

Dimensions in Inches (mm)